

## HIGH SENSITIVITY AC LEAKAGE CLAMP METER

MS2006B/MS2007B

### Features:

- ▶ Jaw Size up to  $\Phi 31\text{mm}/1.2''$
- ▶ 2000 Counts LCD Display
- ▶ MS2006B: Current Measurement from 0.01mA to 60A
- ▶ MS2007B: Current Measurement from 1mA to 150A
- ▶ Data Hold

EMC  
LVD



### Specifications

MS2006B MS2007B

| Specifications            | Range                           | Accuracy   |            |
|---------------------------|---------------------------------|------------|------------|
| AC Current<br>(50Hz~60Hz) | 2mA/20mA/60A                    | ±(2.0%+5)  |            |
|                           | 200mA/2A/150A                   | ±(2.0%+5)  |            |
| Features                  |                                 |            |            |
| Display                   | counts                          | 2000       | 2000       |
| Jaw Opening               |                                 | Φ31mm/1.2" | Φ31mm/1.2" |
| Data Hold                 |                                 | ●          | ●          |
| Low Battery Display       |                                 | ●          | ●          |
| General                   |                                 |            |            |
| Power Supply              | 2x1.5V AAA Batteries            |            |            |
| Product Size              | 176mm×59mm×29mm/6.9"×2.3"×1.14" |            |            |
| Product Weight            | 136g/0.3lb                      |            |            |
| Safety Rating             | CE CAT.II 600V RoHS             |            |            |



**MS2006B**

**JAW SIZE**  
 $\Phi 31\text{mm}/1.2''$

**CURRENT**  
AC 60A



**MS2007B**

**JAW SIZE**  
 $\Phi 31\text{mm}/1.2''$

**CURRENT**  
AC 150A

